



C3-series


IP-basedDoor Access Control Panel



C3-400



C3-200



C3-100

Choice of Readers

Support full range of cardreaders. ZK KR-Series readers are stylish and waterproof. C3 supports any wiegand-output reader, including HID Prox, iClass, and XceedID Multi-Technology.



Communication

C3controllers can beinstalled easily on your network and support TCP/IP communications. Auto-discovery tool allows setting and modification of network parameters directly and easily.



Lowest Total Cost of Ownership

Savecost.C3 controller firmwares can be upgraded without any advanced tools. New features can extend and expand the value of your investment.



Capacity

Supportup to 30,000 badge users and store up to 100,000 events and transactions. Data is preserved if power is lost. Controller continues to operate if network connection is interrupted.



More than Door Control

Accessadditionalcontroland interface. After programming, auxiliary relays can be functioned as lights, alarms and intrusion detection panels. Extra locking devices or gate controllers can be accessed.



Options

C3controllers come in 3 sizes to suit project needs and reduce the cost of unused capacity. 1-door, 2-door, and 4-door models can be mixed and matched in an optimized system architecture, devices or gate controllers.



Built-In Advanced Access Control

Anti-Passback, First-CardOpening, Multi-Card Opening, Duress Password Entry, and Auxiliary Input/ Output linkages are built into controller firmware.



For Software Developers

FreeSDK is available forintegrators and OEM's to integrate the C3 controller with their or existing security or personnel management applications. Upon request, ZK can customize C3 firmware to meet any customer requirements.



Optional Accessories



CR20E/M



RFID Reader



Exit Button




Power Supply



Electric Lock



RS232 485



Alarm



Sensor




Prox Card



Key Fob

Typical Installation



Item	Description	Quantity
C3-100/200/400 Package B		
C3-100/200/400	Control Panel	1 ea 1 ea 1
Case01	Metal Case	ea
ZKPSM030B	Power Supply, DC12V/3A, Available to Charge for BAttery Back-Up	
FR107	Diode for Lock	1
Key	Key for Metal Case	ea
ZKAccess CD	Access Software for Control Panel, User Manual	2
	3.35-3.55kg	ea
Gross Weight	345(L)×70(H)×280(W)mm	1
Dimensions		ea

Specifications

	C3-100	C3-200	C3-400
Number of Doors Controlled	1Door 2 26-bit Wiegand, others upon request	2 Door	4 Door
Number of Readers Supported	2 (Exit Device and Door	4	4 26-bit Wiegand, others upon request
Types of Readers Supported	Status) 2 (1-From C Relay for Lock	26-bit Wiegand, others upon request	12 (4 Exit Device, 4 Door Status, 4
Number of Inputs	and 1-Form C Relay for Aux Output)	6 (2 Exit Device, 2 Door Status, 2 AUX)	AUX) 8 (4-Form C Relay for Lock and
Number of Outputs	30,000	4 (2-From C Relay for Lock and 2-Form C Relay for Aux Output)	4-Form C Relay for Aux Output)
Card Holders Capacity	100,000	30,000	30,000
Log Events Capacity	7.4lbs (3.35kg)	100,000	100,000
Weight	TCP/IP and RS-485*	7.5lbs (3.4kg)	7.8lbs (3.55kg)
Communication	Powder Coated Aluminium	TCP/IP and RS-485*	TCP/IP and RS-485*
Enclosure	Wall Mount	Powder Coated Aluminium	Powder Coated Aluminium
Mounting	12V DC, 1.5A	Wall Mount	Wall Mount
Recommended Power Supply	15in.×3.15in.×11in. 380mm(L) X 80mm(W) X 280mm(H)	12V DC, 1.5A	12V DC, 1.5A
Dimensions (Bundle Only)	6.3in.×4.17in. (160mm×106mm)	15in.×3.15in.×11in. 380mm(L)×80mm(W)×280mm(H)	15in.×3.15in.×11in. 380mm(L)×80mm(W)×280mm(H)
Dimensions (Board Only)		6.3in.×4.17in. (160mm×106mm)	6.3in.×4.17in. (160mm×106mm)